

TABLE 10.1 Basic Dimensions of Unified Screw Threads

Size	Coarse Threads UNC				Fine Threads UNF		
	Major Diameter $d$ (in.)	Threads per Inch	Minor Diameter of External Thread $d_r$ (in.)	Tensile Stress Area $A_s$ (in. <sup>2</sup> )	Threads per Inch	Minor Diameter of External Thread $d_r$ (in.)	Tensile Stress Area $A_s$ (in. <sup>2</sup> )
0(.060)	0.0600	—	—	—	80	0.0447	0.00180
1(.073)	0.0730	64	0.0538	0.00263	72	0.0560	0.00278
2(.086)	0.0860	56	0.0641	0.00370	64	0.0668	0.00394
3(.099)	0.0990	48	0.0734	0.00487	56	0.0771	0.00523
4(.112)	0.1120	40	0.0813	0.00604	48	0.0864	0.00661
5(.125)	0.1250	40	0.0943	0.00796	44	0.0971	0.00830
6(.138)	0.1380	32	0.0997	0.00909	40	0.1073	0.01015
8(.164)	0.1640	32	0.1257	0.0140	36	0.1299	0.01474
10(.190)	0.1900	24	0.1389	0.0175	32	0.1517	0.0200
12(.216)	0.2160	24	0.1649	0.0242	28	0.1722	0.0258
$\frac{5}{16}$	0.2500	—	0.1887	0.0318	28	0.2062	0.0364
$\frac{3}{8}$	0.3125	18	0.2443	0.0524	24	0.2614	0.0580
$\frac{7}{16}$	0.3750	16	0.2983	0.0775	24	0.3239	0.0878
$\frac{1}{2}$	0.4375	14	0.3499	0.1063	20	0.3762	0.1187
	0.5000	13	0.4056	0.1419	20	0.4387	0.1599
$\frac{9}{16}$	0.5625	12	0.4603	0.182	18	0.4943	0.203
$\frac{5}{8}$	0.6250	11	0.5135	0.226	18	0.5568	0.256
$\frac{3}{4}$	0.7500	10	0.6273	0.334	16	0.6733	0.373
$\frac{7}{8}$	0.8750	9	0.7387	0.462	14	0.7874	0.509
1	1.0000	8	0.8466	0.606	12	0.8978	0.663
$1\frac{1}{8}$	1.1250	7	0.9497	0.763	12	1.0228	0.856
$1\frac{1}{4}$	1.2500	7	1.0747	0.969	12	1.1478	1.073
$1\frac{3}{8}$	1.3750	6	1.1705	1.155	12	1.2728	1.315
$1\frac{1}{2}$	1.5000	6	1.2955	1.405	12	1.3978	1.581
$1\frac{3}{4}$	1.7500	5	1.5046	1.90			
2	2.0000	$4\frac{1}{2}$	1.7274	2.50			
$2\frac{1}{4}$	2.2500	$4\frac{1}{2}$	1.9774	3.25			
$2\frac{1}{2}$	2.5000	4	2.1933	4.00			
$2\frac{3}{4}$	2.7500	4	2.4433	4.93			
3	3.0000	4	2.6933	5.97			
$3\frac{1}{4}$	3.2500	4	2.9433	7.10			
$3\frac{1}{2}$	3.5000	4	3.1933	8.33			
$3\frac{3}{4}$	3.7500	4	3.4433	9.66			
4	4.0000	4	3.6933	11.08			

Note: See ANSI standard B1.1-1974 for full details. Unified threads are specified as " $\frac{1}{2}$  in.-13UNC," "1 in.-12UNF."